




# El Cajon Valley SCM


- Surface Topography
- Surface water drainage patterns
- Geology
- Historic Groundwater Development
- Current Groundwater Development
- General Observation







# GENERALIZED GEOLOGIC CROSS-SECTIONS





# Groundwater Development


- Mid-1800s agricultural uses.
- Early 1900s shift to mixed agricultural & domestic uses.
- Mid-1900s the peak use of groundwater was reached within the basin.
- Today Groundwater is being used for public, domestic and industrial supply

# **Groundwater Elevations - Fall 1914** 3000 Feet Copy write 2003, DEH-SAM (c) SanGIS 1955, State of California Department of Public Works, Division of Water Resources

# **Groundwater Elevations - Fall 1952**









# Supply Well Development


Permitted Supply Wells since 1974

Permitted & Published Well





# **General Observations**



### Fletcher Well #4

#### aka - San Diego #4 and El Cajon #4



- Drilled 1952 to 847 feet.
  10" diameter, 91 ft casing
- Static water 31 ft
- PCE + TCE 15 ppb in pumped water
- New well drilled 1997 to 906 feet, 110 ft casing
- Static water 39 ft
- PCE + TCE 20 ppb in pumped water
- Pumps 250 gpm May to December


Fletcher Well – Not Pumping OFFICE EL CAJON PUBLIC WORKS OFFICE & MAINTENANCE 374.92 1060 VERNON WAY 374.77 GRASS PARKING LOT **₩W-19 FORMER** PLANTER **GRASS USTs** VERNON WAY 375.43 water-375.71 375.29 375.69 376:48 MW-18 **PARKWAY** INDUSTRIAL MW-17 CENTER MW-8 STORAGE 943-983 **VERNON** 375.89 WAY 376.19 EQUIPMENT 1000-1069 376.75 **VERNON WAY** ARRIETA CONSTRUCTIO CONCRETE TRASH ASPHALT SCALE (FEET)


NORTH MARSHALL AVENUE

### Site 1 – Groundwater


Fletcher Well – Pumping GROUNDWATER GRADIENT DETERMINED BY 3-POINT OFFICE CAJON PUBLIC WORKS OFFICE & MAINTENANCE 373.30 YARD 1060 VERNON WAY 372.65 MW-20 **GRASS** PARKING LOT **GRASS** USTs VERNON WAY 369.51 372.63 no water. no water NORTH MARSHALL AVENUE 369,46 no wate PARKWAY INDUSTRIAL MW-17 CENTER FORMER 943-983 USTs 370.99 CONCRETE VERNON WAY GARAGE 1000-1069 371.50 VERNON WAY ARRIETA CONSTRUCTION CONCRETE TRASH **3ROUNDWATER** ASPHALT


### Site 1 – GW Elevation vs Pumping





# Site 2 – GW Elevation vs Pumping





### Site 3

- Waste solvents to 12 ft deep sump (1954 - 1983)
- Bottom of sump on DG at watertable
- 5000 ft long TCE plume delineated 1998
- Transport in alluvium and DG
- Darcy Groundwater velocity is 180 ft/yr
- TCE velocity at least 110 ft/yr

# Site 3 - TCE Plume (1000 ppb TCE)



### CONCLUSIONS

- Friars can produce perched zones, but is not contiguous across the valley
- If no Friars formation, expect rapid contamination of GW
- Shallow GW flow toward center of valley, then Northwest
- Horizontal GW velocity 150 ft/yr in alluvium and DG
- Pumping from fractured rock influences portions of shallow aquifer
- Shallow contamination drawn downward by pumping

# SUGGESTIONS

- Distinguish alluvium, Friars and DG
- Use conventional geologic description of core materials
- Do not cross-connect lithologies with long well screens
- Be aware of GW flow velocity when spacing wells
- Check for production wells in area
- Watch monitoring data for cyclic changes in GW elevation